

**Minutes of the:
held in:
on:**

**Ecma TC39-TG1
Phone Conference
3rd March 2006**

Attendees

- Lars T. Hansen, Opera Software
- Graydon Hoare, Mozilla Foundation
- Blake Kaplan, Mozilla Foundation
- Brendan Eich, Mozilla Foundation
- Jeff Dyer, Adobe Systems
- Dan Smith, Adobe Systems
- Francis Cheng, Adobe Systems
- Ed Smith, Adobe Systems

Agenda

- Introductions, Maciej Stachowiak.
- Organize this agenda to fit in one hour (Mozilla people have a stop at noon).
- From last meeting:
 - Go through [proposals](#).
 - Start with [Ed's proposal](#), study it before the meeting.
 - Particular attention to class Class.
 - Go through [recent changes](#).
- Hand out action items by end of meeting
 - so we can parallelize more and avoid serializing through long call-in meetings.

Notes

- Going over [mid-level issues](#).
 - Graydon annotating status on these
 - Everyone to comment on [iterators and generators](#)
 - Brendan to do something on enumerability
- Ed's Edition 3 in Edition 4 proposal
 - `this:T` for unbound method declarations, needed for function type signatures too
 - But what does it mean, and why is it used outside of `dynamic prototype function`?
 - Two issues: where the function is stored, how it binds `this`
 - Assumption is that it's not useful to bind `this` only to a prototype, so `prototype` unbinds `this` in addition to saying where the function is stored
 - Perhaps use more attributes like `{DD, DE, RO}` to talk about where-bound and how-this-constrained

